

MOTOSCREED™

Application Data Sheet

WORKMASTER®

WE FIND A WAY — OR MAKE ONE!



PRINT



SUBMIT

1 of 2

I. CUSTOMER INFORMATION

Company: _____

Date: _____

Contact: _____

Ph: _____

Title: _____

Ext: _____

Address: _____

Em: _____

City, St, Zip: _____

II. GENERAL INFORMATION

1. What does the MOTOSCREED need to accomplish? (Check all that Apply):

- Embed Aggregate
 Remove Bug Holes From Face
 Smooth/Leveling of Surface
 Bring Additional Cream to Surface
 Other: _____

2. Replacing a Current Screed? Yes No If Yes, Type?: _____3. If Yes, What are the Problems/Issues with your Current Screed?:
_____4. Is a Bull Float used in Current Process? Yes No If Yes, Type? Vibrating Non-Vib5. If Yes, When? After Screeding Before Screeding


III. FORM INFORMATION

1. Type of Work? (Check all that apply):

- Flat Slabs Wall Panels Architectural Panels Insulated Panels Superior Walls® Panels
 Double T's Bridge Decks Spandrel Beams NEXT Beams, Prep f/ Stamped Panels
 Singular Products Sound Barriers

2. Is the Product Insulated? Yes No

3. Avg. Form Length: ____' ____" Width: ____' ____" Depth: ____"

4. Type of Form? Steel Wood Rubber Other: _____5. Can MOTOSCREED Control Arms Rest on Edges of Form During Operation? Yes No

If No, Explain: _____

6. Are There Rebar Protrusions or other Form Obstructions That Screed will Encounter?

 No Yes If Yes, Explain: _____
7. Location of Use? Indoor Outdoor

8. Typical Temperature When In Use? Summer: _____ °F °C Winter: _____ °F °C

MOTOSCREED™

Application Data Sheet



IV. CONCRETE INFORMATION

1. Concrete Type:

- Conventional Slump Test: _____ Slump Range: _____
- Self-Compacting Flow Test: _____ Flow Range: _____
- High-Flow Slump Test : _____ Flow Test: _____ Slump/Flow Range: _____

2. Additives


- Micro-Fibers Type: _____ % of Mix: _____ %
- Chemical Additives Type: _____ % of Mix: _____ %
- Light Weight Aggregate Type: _____ % of Mix: _____ %

IV. ELECTRIC INFORMATION

1. Electric Power Available:

- 120V/60Hz/1P 220V/60Hz/3P 330V/60Hz/3P
- 220V/50Hz/1P 220V/50Hz/3P Other: _____

2. Based on Location of Electrical Power, which side should the Switch Box be mounted?



3. Cord Length Needed from Screed to Power Source?: _____ Feet Yards

V. ADDITIONAL INFORMATION/COMMENTS

Note: The **MOTOSCREED** glides along the Form's rails on the Steel Control Arms. When determining size, choose a length that can be used on multiple Forms but with no more than 1ft of Beam overhang on each side of the Form to limit dissipation of vibration caused by Screed flexure, eg, a 10ft Screed for a 10ft Form will also work will on an 8ft Form, but not a 6ft Form. When orking in close quarters be sure to consider that the 2 handles on the Screed will add a total of 14in to the length, eg, a 10ft **MOTOSCREED** have an overall length of 11ft-2in.